


# DX-1200

13/12th Gen. Intel® Core Series High Performance and Compact Rugged Embedded Computer



## MAX. PERFORMANCE | MIN. FOOTPRINT

DX-1200, 12<sup>th</sup> Gen. Intel Alder Lake-S Rugged Embedded Computer

### Overview

[CONTACT](#)

The DX-1200 is a fanless embedded computer that packs extreme performance into a rugged, compact chassis, making it the ideal choice for smart manufacturing, machine vision, and edge AI applications. 13th/12th gen Intel® Core™ (Raptor Lake-S/Alder Lake-S) processor (TDP up to 65W) and DDR5 4800 MHz memory provide high-speed computing performance, while additional functions, including rich native I/O and modular expansion design, meet the requirements for a wide range of applications.

### Key Features

- Intel® 13/12th Gen (Raptor Lake-S/Alder Lake-S) Core™ i9/i7/i5/i3 Processors (max 65 W TDP)
- 2 x DDR5 SO-DIMM Sockets, Supports ECC/non ECC type Memory, Up to 4800MHZ, 64GB
- Quad Independent Display (HDMI / DP / DVI-I)
- 1x M.2 Key E Type 2230 Socket for Intel CNVi / Wireless Module
- CMI Technology for Optional I/O Module Expansions
- CFM Technology for Power Ignition Sensing & PoE Function
- Wide Operating Temperature -40°C to 70°C
- Safety Standard: UL, cUL, CB, IEC, EN 62368-1

### Certifications




### Rapid Processing and Inference

The DX-1200 supports 13/12th gen Intel® Core™ i9/i7/i5/i3 (Raptor Lake-S/Alder Lake-S) processors based on the Intel 7 process, with up to 24 cores (8P + 16E) and 32 threads, delivering more than 1.35x the speed of Comet Lake-S platform. The Intel® Xe architecture of the UHD 770 graphics chip boosts GPU image classification inference performance to 2.8x the speed of Comet Lake-S, providing the processing performance needed for AI and edge computing.

#### CPU Performance



#### GPU Image Classification Inference Performance




### DDR5 ECC Memory

### High-speed, Safe Memory

Two DDR5 SO-DIMM slots support up to 64GB of 4800MHz memory and include ECC (Error Correction Code) technology, giving the extra stability and reliability needed for industrial automation applications.

### Rich and Diverse Expandability

To cater to the widest range of industrial applications, the DX-1200 provides one M.2 Key E slot and two Mini PCIe slots for the addition of WiFi, GNSS, 4G, and Bluetooth. The Mini PCIe slots also support I/O expansion cards, frame grabber cards, and more, to meet different application requirements.



### High-speed, Reliable Data Transmission

To improve the transfer rate of videos or large files, the DX-1200 supports up to four high-speed 10Gbps LAN ports. And for application environments that require multiple network connections, the DX-1200 supports up to 8x PoE, providing data and power through the same cable to reduce the difficulty of wiring.

### Robust and Reliable

The DX-1200 is built tough, reflected in its industrial-grade protection design and industry certifications in different fields. In addition to features such as wide temperature (-40 - 70°C), wide voltage input (9 - 48 VDC), overvoltage, overcurrent, and ESD protection, it also complies with the US military shock vibration standard MIL-STD-810G. Product safety and reliability are further ensured with internationally recognized UL 62368-1 safety certification. For more secure railway computing, it also passes the EMC EN 50121-3-2 standard in EN 50155 and the EN 45545-2 fire protection standard.



## Specifications


| Model Name             | DX-1200   |
|------------------------|---|
| <b>System</b>          |   |
| Processor              | <ul style="list-style-type: none"> <li>13th Generation Intel® Raptor Lake-S Series CPU:                             <ul style="list-style-type: none"> <li>- Intel® Core™ i9-13900E 24 Cores Up to 5.2 GHz, TDP 65W</li> <li>- Intel® Core™ i7-13700E 16 Cores Up to 5.1 GHz, TDP 65W</li> <li>- Intel® Core™ i5-13500E 14 Cores Up to 4.6 GHz, TDP 65W</li> <li>- Intel® Core™ i5-13400E 10 Cores Up to 4.6 GHz, TDP 65W</li> <li>- Intel® Core™ i3-13100E 4 Cores Up to 4.4 GHz, TDP 60W</li> <li>- Intel® Core™ i9-13900TE 24 Cores Up to 5.0 GHz, TDP 35W</li> <li>- Intel® Core™ i7-13700TE 16 Cores Up to 4.8 GHz, TDP 35W</li> <li>- Intel® Core™ i5-13500TE 14 Cores Up to 4.5 GHz, TDP 35W</li> <li>- Intel® Core™ i3-13100TE 4 Cores Up to 4.1 GHz, TDP 35W</li> </ul> </li> <li>12th Generation Intel® Alder Lake-S Series CPU:                             <ul style="list-style-type: none"> <li>- Intel® Core™ i9-12900E 16 Cores Up to 5 GHz, TDP 65W</li> <li>- Intel® Core™ i7-12700E 12 Cores Up to 4.8 GHz, TDP 65W</li> <li>- Intel® Core™ i5-12500E 6 Cores Up to 4.5 GHz, TDP 65W</li> <li>- Intel® Core™ i3-12100E 4 Cores Up to 4.2 GHz, TDP 60W</li> <li>- Intel® Core™ i9-12900TE 16 Cores Up to 4.8 GHz, TDP 35W</li> <li>- Intel® Core™ i7-12700TE 12 Cores Up to 4.7 GHz, TDP 35W</li> <li>- Intel® Core™ i5-12500TE 6 Cores Up to 4.3 GHz, TDP 35W</li> <li>- Intel® Core™ i3-12100TE 4 Cores Up to 4.0 GHz, TDP 35W</li> <li>- Intel® Pentium® G7400E 2 Cores Up to 3.6 GHz, TDP 46W</li> <li>- Intel® Pentium® G7400TE 2 Cores Up to 3.0 GHz, TDP 35W</li> <li>- Intel® Celeron® G6900E 2 Cores Up to 3.0 GHz, TDP 46W</li> <li>- Intel® Celeron® G6900TE 2 Cores Up to 2.4 GHz, TDP 35W</li> </ul> </li> </ul> |
| Chipset                | <ul style="list-style-type: none"> <li>Intel R680E Chipset</li> </ul>   |
| Memory                 | <ul style="list-style-type: none"> <li>2x DDR5 4800 MHz SO-DIMM Socket, Supports Un-buffered and ECC Type, Up to 64GB</li> </ul>  |
| BIOS                   | <ul style="list-style-type: none"> <li>AMI BIOS</li> </ul>  |
| <b>Graphics</b>        |   |
| Graphics Engine        | <ul style="list-style-type: none"> <li>Integrated Intel® UHD Graphics 770: Core™ i9/i7/i5</li> <li>Integrated Intel® UHD Graphics 730: Core™ i3</li> <li>Integrated Intel® UHD Graphics 710: Pentium®/Celeron®</li> </ul>   |
| Maximum Display Output | <ul style="list-style-type: none"> <li>Supports Quad Independent Display</li> </ul>   |
| DVI                    | <ul style="list-style-type: none"> <li>1x DVI-I Connector                             <ul style="list-style-type: none"> <li>- VGA: 1920 x 1080 @ 60 Hz</li> <li>- DVI-D: 1920 x 1200 @ 60 Hz</li> </ul> </li> </ul>  |
| DP                     | <ul style="list-style-type: none"> <li>1x DP Connector: 4096 x 2304 @ 60Hz</li> <li>* Verified maximum resolution: 3840 x 2160 @ 60Hz</li> </ul>  |
| HDMI                   | <ul style="list-style-type: none"> <li>1x HDMI Connector: 3840 x 2160 @ 30Hz</li> </ul>   |
| <b>Audio</b>           |   |
| Audio Codec            | <ul style="list-style-type: none"> <li>Realtek® ALC888, High Definition Audio</li> </ul>  |
| Line-out               | <ul style="list-style-type: none"> <li>1x Line-out, Phone Jack 3.5mm</li> </ul>   |
| Mic-in                 | <ul style="list-style-type: none"> <li>1x Mic-in, Phone Jack 3.5mm</li> </ul>   |
| <b>I/O</b>             |   |
| LAN                    | <ul style="list-style-type: none"> <li>2x 1GbE LAN, RJ45(Supports Wake on LAN, PXE)                             <ul style="list-style-type: none"> <li>- GbE1: Intel® I219</li> <li>- GbE2: Intel® I210</li> </ul> </li> </ul>  |
| COM                    | <ul style="list-style-type: none"> <li>4x RS-232/422/485 with Auto Flow Control (Supports 5V/12V), DB9</li> </ul>   |
| USB                    | <ul style="list-style-type: none"> <li>4 x USB 3.2 Gen2x1 (10Gbps), Type A</li> <li>4 x USB 3.2 Gen1x1 (5Gbps), Type A</li> </ul>   |

|   |   |
|---|---|
| <b>Storage</b>                          |   |
| SSD/HDD                                 | • 2x 2.5" SATA HDD/SSD Bay (SATA 3.0)   |
| mSATA                                   | • 2x mSATA Socket (SATA 3.0, shared by Mini-PCIe socket )   |
| RAID                                    | • Support RAID 0/1/5/10   |
| <b>Expansion</b>                        |   |
| Mini PCI Express                        | • 2x Full-size Mini-PCIe Socket   |
| M.2 E Key Socket                        | • 1x M.2 Key E Type 2230 Socket, Support Intel CNVi Module  |
| SIM Socket                              | • 1x SIM Socket   |
| CMI (Combined Multiple I/O) Interface   | • 2x High Speed CMI Interface for optional CMI Module Expansion<br>• 1x Low Speed CMI Interface for optional CMI Module Expansion |
| CFM (Control Function Module) Interface | • 1x CFM IGN Interface for optional CFM-IGN Module Expansion  |
| <b>Other Function</b>                   |   |
| External FAN Connector                  | • 1x External FAN Connector, 4-pin Terminal Block (Support Smart Fan by BIOS)   |
| Clear CMOS Switch                       | • 1x Clear CMOS Switch  |
| Reset Button                            | • 1x Reset Button   |
| Instant Reboot                          | • Support 0.2sec Instant Reboot Technology  |
| Watchdog Timer                          | • Software Programmable Supports 256 Levels System Reset  |
| <b>Power</b>                            |   |
| Power Button                            | • 1x ATX Power On/Off Button  |
| Power Mode Switch                       | • 1x AT/ATX Mode Switch   |
| Power Input                             | • 9-48VDC, 3-pin Terminal Block   |
| Remote Power On/Off                     | • 1x Remote Power On/Off, 2-pin Terminal Block  |
| Max. Power Consumption                  | • 35WCPU: 201.17W<br>• 65WCPU: 274.80W<br>- Test conducted with CPU, 1x RAM, and 1x storage<br>- 100% load during burn-in testing |
| Inrush Current (Peak)                   | • 35W CPU: 4.151 A@24V<br>• 65W CPU: 4.360 A@24V  |
| <b>Physical</b>                         |   |
| Dimension ( W x D x H )                 | • 242 x 173 x 75 mm   |
| Weight Information                      | • 3.05 kg   |
| Mechanical Construction                 | • Extruded Aluminum with Heavy Duty Metal   |
| Mounting                                | • Wall / DIN-RAIL / VESA / Side Mount   |
| Physical Design                         | • Fanless Design<br>• Cableless Design<br>• Jumper-less Design<br>• Unibody Design  |
| <b>Reliability &amp; Protection</b>     |   |
| Reverse Power Input Protection          | • Yes   |
| Over Voltage Protection                 | • Protection Range: 51~58V<br>• Protection Type: shut down operating voltage, re-power on at the preset level to recover          |
| Over Current Protection                 | • 15A   |


|                         |   |
|-------------------------|---|
| CMOS Battery Backup     | <ul style="list-style-type: none"> <li>• SuperCap Integrated for CMOS Battery Maintenance-free Operation</li> </ul>   |
| MTBF                    | <ul style="list-style-type: none"> <li>• 394,488 Hours - Database: Telcordia SR-332 Issue3, Method 1, Case 3</li> </ul>   |
| <b>Operating System</b> |   |
| Windows                 | <ul style="list-style-type: none"> <li>• Windows®11, Windows® 10</li> </ul>   |
| Linux                   | <ul style="list-style-type: none"> <li>• Ubuntu Desktop 22.04 LTS</li> </ul>  |
| <b>Environment</b>      |   |
| Operating Temperature   | <ul style="list-style-type: none"> <li>• 35W TDP Processor: -40°C to 70°C</li> <li>• 65W TDP Processor: -40°C to 50°C (With External Fan Kit)</li> <li>- With extended temperature peripherals; Ambient with air flow</li> <li>- According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14</li> </ul>  |
| Storage Temperature     | <ul style="list-style-type: none"> <li>• -40°C to 85°C</li> </ul>   |
| Relative Humidity       | <ul style="list-style-type: none"> <li>• 95% RH @ 70°C (Non-condensing)</li> </ul>  |
| Shock                   | <ul style="list-style-type: none"> <li>• MIL-STD-810G</li> </ul>  |
| Vibration               | <ul style="list-style-type: none"> <li>• MIL-STD-810G</li> </ul>  |
| EMC                     | <ul style="list-style-type: none"> <li>• CE, UKCA, FCC, ICES-003 Class A</li> <li>• EN 50155 (EN 50121-3-2 Only)</li> <li>• E-Mark</li> </ul>   |
| EMI                     | <ul style="list-style-type: none"> <li>• CISPR 32 Conducted &amp; Radiated: Class A</li> <li>• EN/BS EN 50121-3-2 Conducted &amp; Radiated: Class A</li> <li>• EN/BS EN IEC 61000-3-2 Harmonic current emissions: Class A</li> <li>• EN/BS EN61000-3-3 Voltage fluctuations &amp; flicker</li> <li>• FCC 47 CFR Part 15B, ICES-003 Conducted &amp; Radiated: Class A</li> </ul>   |
| EMS                     | <ul style="list-style-type: none"> <li>• EN/IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV</li> <li>• EN/IEC 61000-4-3 RS: 80 MHz to 1000 MHz: 20 V/m</li> <li>• EN/IEC 61000-4-4 EFT: AC Power: 2 kV; Signal: 2 kV</li> <li>• EN/IEC 61000-4-5 Surges: AC Power: 2 kV</li> <li>• EN/IEC 61000-4-6 CS: 10V</li> <li>• EN/IEC 61000-4-8 PFMF: 50 Hz, 1A/m</li> <li>• EN/IEC 61000-4-11 Voltage Dips &amp; Voltage Interruptions: 0.5 cycles at 50 Hz</li> </ul> |
| Safety                  | <ul style="list-style-type: none"> <li>• UL, cUL, CB, IEC, EN 62368-1</li> </ul>  |
| Fire Protection         | <ul style="list-style-type: none"> <li>• EN 45545-2</li> </ul>  |

**External Layout**


Front I/O



Rear I/O



**Dimensions**



Unit: mm

## Ordering Information

### Available Models

| Model No.   | Description   |
|-------------|---|
| DX-1200-R10 | 13/12th Gen. Intel® Core Series High Performance and Compact Rugged Embedded Computer |

### Package Checklist


|                              |  |
|------------------------------|--|
| • DX-1200 Rugged Computer x1 | • Power Terminal Block Connector x1                |
| • CPU Heatsink Pack x1       | • Remote Power On/Off Terminal Block Connector x 1 |
| • Screw Pack x 1             | • Fan Terminal Block Connector x 1                 |
| • Wall Mounting Kit x1       | • DVI-I to VGA Adaptor x 1                         |










### Optional Modules and Accessories

| Model No.         | Description   |
|-------------------|---|
| CFM-PoE01         | CFM Module with PoE Control Function, Individual Port 25.5W                   |
| CFM-IGN01         | CFM Module with Power Ignition Sensing Control Function, 12V/24V Selectable   |
| CMI-LAN01-R12     | CMI Module with 4x RJ45 Intel I210 1GbE LAN Ports                             |
| CMI-10GLAN05-R10  | CMI Module with 2x Intel 10GbE LAN, RJ45 Port                                 |
| CMI-M12LAN01-R12  | CMI Module with 4 x M12 Intel I210 1GbE LAN Ports                             |
| CMI-XM12LAN01-R10 | CMI Module with M12 X-Coded Connector, 4x Intel I210 1GbE LAN Ports           |
| CMI-DIO01         | CMI Module with 16DIO (8in 8out)  |
| CMI-COM01         | CMI Module with 2x RS232/422/485 (Support 5V/12V)                             |
| MEC-COM-M212-TDB9 | Mini-PCIe Module with 2x RS-232 Serial Ports, 1x Thin DB9 Cable               |
| MEC-COM-M334-TDB9 | Mini-PCIe Module with 4x RS-232/422/485 Serial Ports, 2x Thin DB9 Cable       |
| MEC-LAN-M102-30   | Mini-PCIe Module with 2x LAN Ports, 2x 30cm cable                             |
| UB0930-R10        | Universal Bracket with 4x M12 X-Coded Cutout                                  |
| UB1303            | Universal Bracket with 2x DB9 Cutout  |
| UB1311            | Universal Bracket with 2x RJ45 Cutout for MEC-LAN Expansion                   |
| UB1318            | Universal Bracket with DIO Cutout   |
| UB1710-R10        | Universal Bracket with 4x M12 A-Coded Cutout                                  |
| UB1712-R10        | Universal Bracket with 4x RJ45 Cutout   |
| UB1728-R10        | Universal Bracket with 2x RJ45 Cutout for CMI-10GLAN Expansion                |
| SIDE-DX           | DX Series side mount kit  |
| DIN01             | DIN-RAIL Mount Kit, KMRH-K175   |
| GST120A24-CIN     | Adapter AC/DC 24V 5A 120W with 3pin Terminal Block Plug and Tubes, Level VI   |
| GST220A24-CIN     | Adapter AC/DC 24V 9.2A 220W with 3pin Terminal Block Plug and Tubes, Level VI |

|               |  |
|---------------|--|
| GST360A24-CIN | Adapter AC/DC 24V 15A 360W with 3pin Terminal Block Plug and TUBES, Level VI       |
| RSD-200D-24   | Railway Single Output DC-DC Converter 200W / DC 24V                                |
| FAN-EX101     | External Fan with 4pin Terminal Block Plug and Mounting Bracket, Support smart fan |

**Optional Module Configuration**



| Model No.   | Description  | 1 | 2 | 3 | 4 |
|---|--|---|---|---|---|
| CMI-LAN01-R12/UB1712-R10<br>       | CMI Module with 4x Intel I210 1GbE LAN, RJ45 Port / Universal Bracket with 4x RJ45 Cutout                          | V | V | - | - |
| CMI-10GLAN05-R10/UB1728-R10<br>    | CMI Module with 2x Intel 10GbE LAN, RJ45 Port/ Universal Bracket with 2x RJ45 Cutout                               | V | V | - | - |
| CMI-M12LAN01-R12/UB1710-R10<br>  | CMI Module with M12 Connector, 4x Intel 1GbE LAN / Universal Bracket with 4x M12 A-Coded Cutout                    | V | V | - | - |
| CMI-XM12LAN01-R10/UB0930-R10<br> | CMI Module with M12 X-Coded Connector, 4x Intel I210 1GbE LAN Ports / Universal Bracket with 4x M12 X-Coded Cutout | V | V | - | - |
| CMI-DIO01/UB1318<br>             | CMI Module with 16DIO (8in 8out) / Universal Bracket with DIO Cutout   | - | - | - | V |
| CMI-COM01/UB1303<br>             | CMI Module with 2x RS232/422/485 (Support 5V/12V) / Universal Bracket with 2x DB9 Cutout                           | - | - | - | V |
| MEC-COM-M212-TDB9/UB1303<br>     | Mini-PCle Module with 2x RS-232 Serial Ports, 1x Thin DB9 Cable / Universal Bracket with 2x DB9 Cutout             | - | - | V | V |
| MEC-COM-M334-TDB9/2xUB1303<br>   | Mini-PCle Module with 4x RS-232/422/485 Serial Ports, 2x Thin DB9 Cable / 2x Universal Bracket with 2x DB9 Cutout  | - | - | V | V |
| MEC-LAN-M102-30/UB1311<br>       | Mini-PCle Module with 2x LAN Ports, 2x 30cm cable / Universal Bracket with 2x RJ45 Cutout for MEC-LAN Expansion    | - | - | V | - |

V : Compatible